



ARJO ENTERPRISE 8000X - HOSPITAL BED



SKU: N/A

PRODUCT DESCRIPTION

PURPOSE & BENEFITS

The Enterprise 8000X hospital bed delivers significant benefits to the patient, caregiver and healthcare facility.

The daily challenges faced by nursing teams on hospital wards have inspired Arjo to improve upon an established solution, trusted by hospitals around the globe. In the development of the Enterprise 8000X hospital bed, Arjo has focused on key customer needs common to all healthcare environments, namely:

- Comfort for both resident/patient and caregiver.
- Compliance with new international standards.
- Equipment that is robust, intuitive and easy to use.
- Solutions focused on quality of care for residents/patients.

The Enterprise 8000X has been independently tested by a globally renowned organisation, to certify that it is compliant with the latest stability, dimensional and requirements of the IEC60601-2-52 Standard.

FEATURES

Security and comfort

A secure environment is critical to the wellbeing of patients and carers. Falls affect as many as 10% of older adults during an acute care inpatient stay¹ and can result in serious and often life-threatening injuries.

Intuitive operation and easy of use

Our one-button-push controls are intuitive and easy to use, thanks to clear and simple icons. One touch functions can be used for key features, such as:

- Auto CPR
- 30 degree backrest angle
- Auto-contour
- Cardiac chair position
- Low height and extra low height
- Trendelenberg / reverse Trendelenberg

Some or all of these functions may be locked out by the caregiver if required.

Enhancing the quality of care

The backrest will pause when raised to an angle of 30°, ensuring easy and positive backrest adjustment time after time. The caregiver can easily adjust the bed into a cardiac chair position with our simple to use control panel, by selecting the appropriate icon.

Infection control, pit stop maintenance and service

The Enterprise 8000X is designed with open architecture and no base cover to allow easy access for cleaning, decontamination, maintenance and service.

- The blow-moulded decksheets and head/foot panels are lightweight, smooth and easy to remove to aid cleaning.
- Pit stop maintenance is achieved by designing open accessibility and plug and play components. Changes such as actuator, control box and battery can be carried out in situ within a few minutes by one trained person.
- Equipment is designed to be easy to service and maintain, reducing time spent on cleaning, service and maintenance activities.

Optional: Now available with IndiGo

IndiGo is the powered 5th wheel that makes lighter transport available to any caregiver with just a touch – for ease and simplicity. IndiGo is always available and built directly into your Enterprise bed, so only one thing changes in a caregiver's day: the amount of work required to move the bed.

SPECIFICATIONS

Angles

Head down tilt	12°
Foot down tilt	12°
Backrest angle	62°
Backrest pause	30°
Thigh angle	20°
Calf angle	16°

Product

Safe working load kg	250 kg
----------------------	--------

Safe working load lb	551,16 lb
Maximum patient weight kg	185 kg
Maximum patient weight lb	407,86 kg
Safety standard IEC	IEC60601-2-52

Dimensions

Overall standard length (HOD) mm	2300 mm
Overall standard length (HOD) in	90,55 in
Overall standard height (HOB) mm	2350 mm
Overall standard height (HOB) in	92,52 in
Overall width mm	1030 mm
Overall width in	40,55 in
Mattress length standard mm	2020 mm
Mattress length standard in	79,53 in
Mattress width standard mm	880 mm
Mattress width standard in	34,65 in
Overall length, extended (HOD) mm	2420 mm
Overall length, extended (HOD) in	95,28 in
Overall length, extended (HOB) mm	2470 mm
Overall length, extended (HOB) in	97,24 in
Mattress length, extended mm	2140 mm
Mattress length, extended in	84,25 in
Overall length, short (HOD) mm	2190 mm
Overall length, short (HOD) in	86,22 in
Overall length, short (HOB) mm	2240 mm
Overall length, short (HOB) in	88,19 in
Mattress length short mm	1910 mm
Mattress length short in	75,2 in
Top height (with 125 mm castors) mm	760 mm
Top height (with 125 mm castors) in	29,92 in
Low height (with 125 mm castors) mm	320 mm
Low height (with 125 mm castors) in	12,6 in
Backrest length mm	850 mm
Backrest length in	33,46 in
Seat length mm	215 mm
Seat length in	8,46 in
Calf length mm	560 mm

Calf length in	22,05 in
Thigh length mm	365 mm
Thigh length in	14,37 in

Electrical

Ingress protection	IPX4
Shock protection	Class 1, Type B
Power in (230V)	1.25A at 230V
Power in (120V)	2A at 120V
Power in (60Hz)	AC 50/60Hz