



## ARJO MINUET



**SKU:** 100500AUS

## PRODUCT DESCRIPTION

### PURPOSE AND BENEFITS

Designed for use in residential and convalescent homes and private residences, our range of Minuet 2 community beds provides a real solution for independent living. Advanced electrical profiling, variable bed height, combined with a domestic appearance makes the Minuet 2 the natural choice for the private, residential and convalescent home user. To facilitate transport and storage the bed has been designed to be demounted and foldable to minimise space requirements.

[View the Arjo Minuet 2 product brochure](#)

### FEATURES

- Low platform height 250 mm (10") from the floor
- Safe working load 180 kg (396 lbs)
- Electric backrest, knee break and height adjustment
- Pro-Contour Advance profiling feature has demonstrated low interface pressures which may help in the prevention of pressure injuries
- Battery back-up.
- Integrated mattress platform extension of 130 mm (5") with mattress retainer
- Designed for use in private, residential and convalescent homes
- Easy to disassemble into four parts for improved installation access
- Optional two-way tilt; foot-down/head-down\*
- Compact storage/transportation (using transit brackets)
- Wide range of accessories available.

### SPECIFICATIONS

## 160 & 161

Overall length	2250 mm (88.6")
Overall length (extended)	2390 mm (94")
Overall width without safety sides	940 mm (37")
Overall width with safety sides	1050 mm (41.3")
Mattress size (L x W x H)	1980 x 860 x 125 mm (78 x 33.8 x 5")
Height range	250 - 660 mm (9.8 - 26")
Tilt range (if fitted)	+/- 10.8°
Backrest angle (maximum)	69°
Thigh elevation (maximum)	32°
Safe working load	180 kg (396 lbs)
Maximum patient weight	145 kg (319 lbs)
Section weights - Head end	22.8 kg (50 lbs)
Section weights - Foot end	22.8 kg (50 lbs)
Foot end mattress platform section	19.8 kg (44 lbs)
Head end mattress platform section	23.5 kg (52 lbs)
Electrical data (all models)	
Power in	1.7 A max. 120 V a.c. 60 Hz / 1 A max. 230 V a.c. 50 Hz
Electric shock protection	Class II, Type B
Ingress protection	IP24
Battery	12 V, 1.2 Ah sealed rechargeable lead/acid gel