



ARJO SORRENTO - HOMECARE BED



SKU: N/A

PRODUCT DESCRIPTION

PURPOSE AND BENEFITS

The Sorrento range clearly reflects Arjo's awareness of the functional and aesthetic demands of today's healthcare market. With a range of options and accessories available, the Sorrento is a stylish, yet economical choice for any Nursing and Community healthcare environment. Due to the extensive options and features available on the Sorrento range, Arjo is able to customise a bed specific to your requirements.

FEATURES

- Electrically operated lift and backrest adjustment (2 section)
- 125mm central locking system (2 x brake / 1 x track lock / 1 plain)
- Removable sheet metal platform sections for easy cleaning
- Castors central locking activation lever
- Fully moulded undercarriage cover
- Fold down foot panels (range of timber melamine colours available)
- Accessory sockets at head end (for self help pole and IV pole)
- Available in Botegga Oak or Beech

OPTIONAL EXTRAS

- Electrically operated height and back rest and knee bend (4 section model)
- Mechanical calf adjustment (4 section model only)
- Battery backup
- Base extension
- Timber range of drop-in head and foot panels options
- Blow moulded plastic head and foot panels
- Fold-down battalion grab rail

SPECIFICATIONS

Sorrento Floor Bed Single

Overall Length	2115 mm
Overall Length (base extension extended)	2310 mm
Overall Width	920 mm
Overall Width (rails fitted)	1025 mm
Mattress Surface Length (between panels)	2070 mm
Bed Platform Height Range	1700 mm - 690 mm (+/- 5 mm)
Back Rest Angle Adjustment	0° to 70°
Knee Bend Angle Adjustment	0° to 35°
Trendelenberg Tilt Adjustment (head and foot down)	0° to 14°
Safe Working Load	250 kg

Sorrento Floor Bed King Single

Overall Length	2115 mm
Overall Length (base extension extended)	2310 mm
Overall Width	1090 mm
Overall Width (rails fitted)	1200 mm
Mattress Surface Length (between panels)	2070 mm
Bed Platform Height Range	170 mm to 690 mm (+/- 5mm)
Back Rest Angle Adjustment	0° to 70°
Knee Bend Angle Adjustment	0° to 35°
Trendelenberg Tilt Adjustment (head and foot down)	0° to 14°
Safe Working Load	250 kg